



REAR HUB MOTOR

36 V 48 V

HIGH EFFICIENCY HUB MOTORS FROM 250W TO 500W, ENGINEERED FOR DIVERSE RIDING CONDITIONS FROM CITY STREETS TO DEMANDING TRACKS

250-500 W

Geared Hub Motor Range

80 Nm

Max torque for eCargo

IP65 Rated

Dust & water protected for all weather

Compliant

EN-15194 compliant full range

TECHNICAL SPECIFICATIONS

Feature	FOLD	CITY	MTB	CARGO
Type of Use	eFolding	eCity	eMTB	eCargo
Position	Rear	Rear	Rear	Rear
Wheel Size	20"	26"	29"	24"
Rated Power	250 W	250 W	250 W	500 W
Rated Voltage	36 V	36 V	36 V	48 V
Max Torque	50 Nm	50 Nm	50 Nm	80 Nm
Max Speed	25 km/h	25 km/h	25 km/h	25 km/h
Freewheel	7S/8S/9S	7S/8S/9S	7S/8S/9S	7S/8S/9S
Sensor Type	Speed	Speed	Speed	Speed
Weight	2.8 kg	2.8 kg	3.2 kg	4.5 kg
IP Grade	IP65	IP65	IP65	IP65
Operating Temp	-20 / +45°C	-20 / +45°C	-20 / +45°C	-20 / +45°C
Brake Type	Disc	Disc	Disc	Disc

INFINITE SAS

SIREN: 101 499 127
www.gotoinfinite.com
contact@gotoinfinite.com

INFINITE reserves the right to modify the product technical characteristics, without notice. Non-contractual product views and document. INFINITE 2026.